

imotion TopVoyage LED Lean



Anzeige / Sign / Afficheur

Technologie / Technology / Technologie
 LED-Farbe / LED colour / Couleur LED
 Regulierung der LED / Adjustment of LED /
 R glage du LED
 Ablesewinkel / Viewing angle / Angle de visualisation

LED
 Amber / Amber / Ambre
 3stufig manuell / three-step
 Manual /   trois degr s manuel
 +/- 70  (horizontal)

Elektrische Eigenschaften Steuerger t / Electrical features control unit / Caract ristiques  lectriques bo tier de commande

Anzeige / Display / Ecran
 Nennstrom / Nominal current / Curent nominale
 Schnittstellen / Interfaces
 Speicherplatz / Memory / Case m moire

32 x122 Pixel
 80 mA
 Alpha-BUS
 500 KB

Elektrische Eigenschaften Anzeige / Electrical features Sign / Caract ristiques  lectriques afficheur

Nennspannung / Nominal voltage / Tension nominale

24 VDC -30%....+25%

Umgebung / Environment / Environnement

EMV / EMC / CEM 2006/28
 Betriebstemperatur / Operating temperature / Temp rature de service
 Lagertemperatur / Storage temperature / Temp rature de stockage

e1 033280
 -20 C ... 70 C
 -40 C ... 85 C

Mechanik / Mechanics / M canique

Geh use / Housing / Structure

Aluminium / Aluminium
 Stahl / Steel / Acier

Anschlussstecker - gem ss Zeichnung / Connector - see drawing /
 Connecteur - voir le dessin

imotion TopVoyage LED Lean

Monochrome Matrix / Matrice monochrome

Artikelnummer / Item number / Num�ro d'article	Matrix / Matrix / Matrice	Slave	Master	Stand alone	Gewicht / Weight / Poids
07.69.03.00.324	16x35/10			X	2.560 KG
07.69.33.00.320	16x70/10			X	3.160 KG
07.69.33.00.322	16x105/10			X	4.340 KG
07.69.33.00.323	8x105/10			X	folgt/follows/suivra
07.69.33.00.330	16x105/10		X		4.340 KG
07.69.33.00.325	16x70/10		X		folgt/follows/suivra
07.69.33.00.326	8x70/10		X		folgt/follows/suivra
07.69.03.00.329	16x35/10	X			2.460 KG
07.69.33.00.327	16x70/10	X			folgt/follows/suivra
07.69.33.00.330	16x105/10	X			folgt/follows/suivra
07.69.33.00.328	8x70/10	X			folgt/follows/suivra