

imotion video

Innenkameras

Interior camera

Caméra intérieure



Mini Dome



Midi Dome



Dome

Elektrische Eigenschaften / Electrical features / Caractéristiques électriques

Nennspannung / Nominal voltage / Tension nominale		12 VDC
Max. Leistungsaufnahme / Power consumption / Puissance absorbée		
	Dome	2,4 W
	Mini+Midi Dome, Front Cam	1,2 W

Umgebung / Environment / Environnement

Betriebstemperatur / Operating temperature / Température de service		
	Dome / Midi Dome	-10° ... + 60°
	Mini Dome	-10° ... + 60°
	Front Cam	-10° ... + 60°
Bildsensor / Image sensor / Détecteur à formation d'images		1/3" Sony CCD
Lichtempfindlichkeit / Light sensitivity / Photosensibilité		
	Dome	0,1 (LUX)
	Midi Dome	0,5 (LUX)
	Mini Dome	0,2 (LUX)
	Front Cam	0,25 (LUX)
Auflösung / Resolution / Résolution		752 x 582 Pixel

Schnittstelle / Interface / Interface

Stromversorgung / Power supply / Alimentation		AMP 2pol
Video Schnittstelle / Video interface / Interface video		BNC female
Videoausgangs-Signal / Video output signal / Signal de sortie vidéo		FBAS 1Vss
Signal-/Rauschabstand / Signal distance / Distance d'implantation des signaux		> 45dB
Ausgangssignal / Output signal / Sorties		PAL
TV Linien / TV lines / Lignes TV		480
	Dome	550
	Mini+Midi Dome, Front Cam	550

Mechanik / Mechanics / Mécanique

Gehäuse / Housing / Structure		Metall / Metal / Métal
Gehäuseschutz / Housing guard / Structure protection		lackiert / coated / laqué

imotion video Innenkamera / Interior camera / Caméra intérieure

Artikelnummer / Item number / Numéro d'article	Abmessung Dimensions	Objektiv Objective Objectif	IP-Schutzart IP safety class protection	Blickwinkel Diag. Viewing angle diag. Angle de visibilité diag.	Blickwinkel horiz. Viewing angle horiz. Angle de visibilité horiz.	Gewicht / Weight / Poids
195.716 Mini Dome	47 x 44 mm	3,7 mm	IP40	82,5°	66°	0,2 kg
195.721 Midi Dome	80 x 60 mm	4,3 mm	IP41			0,3 kg
195.780 Midi Dome	80 x 60 mm	3,6 mm	IP41	72,5°	58°	0,3 kg
195.781 Midi Dome	80 x 60 mm	2,9 mm	IP41			0,3 kg
195.713 Dome VC1	140 x 95 mm	2,9 mm	IP65	100°	80°	0,79 kg
195.714 Dome VC1	140 x 95 mm	3,6 mm	IP65	84°	67°	0,79 kg
195.715 Dome VC1	140 x 95 mm	4,3 mm	IP65	72,5°	58°	0,79 kg

EMV / EMC / CEM

Mini Dome: e1*72/245*2006/28*5826*01

Midi Dome: E1_R10_03 036161

Dome: e1*72/245*2006/28*5148*01